


Model: 400 Tungsten (PRM-400TU), 400 Daylight (PRM-400DA)

Studio Quality LED Lighting Fixtures for Professional Imaging Applications



- The Lowel Prime LED System has dedicated tungsten as well as daylight color fixtures
- They have powerful output, wide beam angles, and high color rendering indexes
- Fanless convection cooling allows them to vent heat quietly
- At 135 Watts, Prime 400 is more efficient than fluorescent or Tungsten-halogen fixtures
- 50,000 hour manufacturer listed LED lamp life
- All models auto-set to AC voltages from 90-240V
- Most components in fixture are easily user replaceable
- Light Control Accessories available


Application:

The Lowel Prime LED 400 is a professional studio quality LED lighting fixture, in dedicated Daylight (5600°K) or Tungsten (3300°K) color models, with a high Color Rendering Index of 91+. It has a beam angle of 50°, and light output of 43 foot candles at 12 feet. It is fully DMX-512 (1990) compliant, and can be dimmed via DMX or manually on the unit. Daylight models have a small quantity of Tungsten color LEDs, and Tungsten models have a small quantity of Daylight LEDs integrated into their array's, for purposes of color balancing. It is possible to give the 2 colors in each fixture separate DMX addresses, to allow minor adjustment of their relative setup levels, for applications needing color proximity matching to other sources (aprox range, 100-200°K). The fixture consumes 135 Watts, has a power factor of .95, fanless convection cooling for silent operation, and a metal housing. It can be mounted on a stand or hung on a rail. It conforms to UL STD. 1573, and is Certified to CSA STD. C22.2 No. 16 6.

Specification:

Studio LED fixture shall be listed in compliance with UL STD. 1573, and Certified to CSA STD. C22.2 No. 16 6. It shall be DMX dimmable, have a beam angle of 50 degrees, Color Rendering Index of 90+, allow for minor adjustment of output color (daylight or tungsten), fanless convection cooling, and be able to deliver 40 footcandles of light or more at 12 feet.

Performance



Beam Angles:

- Points at which intensity drops to 50% of maximum.
- Foot Candle readings taken with Tungsten color model, at center of beam, using a Minolta CL-200 meter.

Available Accessories:

Honeycomb Grids:

Each fixture has accessory honeycomb grids to control the spill of the light, by attaching easily to the front of the fixture. The grids are available in 20 or 30 degree dispersions. Honeycomb Grids cause some loss of light output

Barndoor/Softening Set


This set includes a 4 way barndoor and subtle diffusion gel. Due to the 'multi point-source' nature of most LED fixtures, it is common to have an undesired multi-shadow effect when using barndoors to trim the beam.



Barndoors with added diffusion attached will minimize multi-shadow, while still allowing a visible barndoor cut.



Model: 400 Tungsten (PRM-400TU), 400 Daylight (PRM-400DA)



Controlling Lowel Prime LED

The fixtures of the Lowel Prime LED Series are all dimmable models, which can be controlled either manually on the fixture or remotely via a console with DMX-512 protocol.

Technical Specifications

General

Use: Dry locations only

Supplied contents: Lowel Prime LED 400, Gel Frame, Safety Cable, Standard C-Clamp, 5/8" Female Stand Fitting, unswitched T1-808 AC Cable, and (USA domestic models only) switched T1-80 AC Cable

Input:

AC POWER INPUT:

USA/Canada: 110-120V, 60Hz, 135W

Worldwide: 100-240V, 60Hz, 135W

Power Factor: .95

Input Voltage	Nominal Current	Peak Current	Fuse
120 VAC	1.076 A	1.5A	3A/250V (USA/Canada)
220 VAC	0.619 A	0.92A	3A/250V (Worldwide)

AMPERAGE: 1.5 Amps at 120 Volts. 0.92 Amps at 220Volts

Color Temperature / CRI

Model 400-DA: 5600°k

Model 400-TU: 3300°k

Color Rendering Index (CRI)

Both Models: 90+ (pro photo quality)

Physical

Dimensions: 24.9 x 3.5 x 14.9" (63.3 x 8.9 x 38 cm)

Weight: 17.5 lbs (8 kg)

Housing: Sheet metal with flat black scratch resistant paint

Heat Management

Heat dissipation: Free convection

Air flow requirements: Allow for free air convection

Data And Installed Software Features

INTERFACE OPTIONS:

Serial: USITT DMX-512, 1990

DMX addressing: On unit, 1–512 addresses.

Software Features

Software Lock: fixture can be password locked to limit access to controls

Master/Slave: 1 master can control multiple DMX chain slaves (all dim together with Master, on unit - no console required).

Color Tweaking: Allows the daylight & tungsten LEDs to be separated, and given DMX addresses, for tweaking output color.

Stored Dimming Behavior Curves: To vary the rate of dimming when using a DMX console, there are 4 stored behavior curves. This allows the fixture to dim at the same rate as conventional fixtures (ex - tungsten-halogen) that are also in the DMX chain.

Agency Approvals

Conforms to UL STD. 1573

Certified to CSA STD. C22.2 No. 16.6.



Warranty

Lowel-Light warrants that Lowel Prime LED fixtures under normal use in accordance with operating instructions, will perform to the specifications published by Lowel-Light at the time of purchase, for two (2) years, from the date of purchase by the consumer. In the event of a defect reported by the consumer within the applicable time period, if any, Lowel-Light will, at its option, replace or repair the defective merchandise at no charge to the consumer for either parts or labor.

Ver 1.1 ©2012, Lowel-Light Manufacturing, Inc.

Lowel Prime is a trademark of Lowel-Light Mfg, Inc.



Lowel-Light Manufacturing, Inc.
 90 Oser Avenue, Hauppauge N.Y. 11788
Tel: 631-273-2500 or 800-645-2522
Fax: 631-273-2557
info@lowel.com
www.lowel.com